



Standard temp range:	-20 to +40
Earthing:	Internal and External earth bolt.
Gland Plates:	Can be delivered on request (Not Standard)
Cable Entries:	Glands in Brass , SS316L, Nickelplated or MCT frames.
Drainplug/Breather:	Delivered upon request. To be installed at lowest point of cabinet (Bottom)

Technical data:

Material:	AISI316L/EN 1.4404
Protection:	IP66/67
Ex-protection:	Ex II 2G Ex e II T6
Finish:	Bright chemical dip
Voltage:	750V
Approval:	Nemko 11ATEX1325

Description:	Dimension (WxHxD)	Fixing Dim. (A x B)		Elcor Part no.	
HT-S 252515	250x250x150	220 x 280		1000.940	
HT-S 253015	250x300x150	220 x 330		1000.941	
HT-S 354515	350x450x150	320 x 480		1000.942	
HT-S 404015	400x400x150	370 x 430		1000.510	
HT-S 405015	400x500x150	370 x 530		1000.511	
HT-S 406015	400x600x150	370 x 630		1000.512	
HT-S 407515	400x750x150	370 x 780		1000.513	

Description:	Dimension (WxHxD)	Fixing Dim. (A x B)		Elcor Part no.	
HT-S 5010020	500x1000x200	470 x 1030		1000.514	
HT-S 606020	600x600x200	570 x 630		1000.515	
HT-S 607520	600x750x200	570 x 780		1000.516	
HT-S 6010020	600x1000x200	570 x 1030		1000.517	

Other sizes
on request

